

# SDS

### Safety Data Sheet PHIFER INCORPORATED

#### SheerWeave Style 4500/4600

SDS Number: PI-SDS-T590

Revision Date: 5/13/2015

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer PHIFER INCORPORATED P.O. Box 1700 Tuscaloosa, AL 35403

Phone:205/345-2120Web:www.Phifer.com

Product Name:SheerWeave Style 4500/4600Revision Date:5/13/2015Version:1SDS Number:PI-SDS-T590Product Code:PI-SDS-T590Product Use:Sun Control

#### 2 HAZARDS IDENTIFICATION

Route of Eyes; Ingestion; Inhalation; Skin;

Entry:

Inhalation: Short-term harmful health affects are not expected from vapor generated during normal use at ambient temperature.

Skin Contact: Fibers in core yarn may irritate skin

Eye Contact: May cause irritation.

Ingestion: Consult physician

GHS Precautionary Statements:

P281 - Use personal protective equipment as required.

P337 - If eye irritation persists: flush with water





#### SheerWeave Style 4500/4600

SDS Number: PI-SDS-T590

Revision Date: 5/13/2015

Page 2 of 5

Ingredients:

3

4

5

COMPOSITION/INFORMATION ON INGREDIENTS

-	<u>WT. %</u>	CAS Registry #
Polyester Core Yarn	17-22	NA
Vinyl Coating	78-83	NA

### OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200): OSHA EXPOSURE LIMITS 8 hrs. TWA (ppm) <u>OSHA PEL</u><u>ACGIH TLV</u>

Polyester Core Yarn:	no restriction	
Vinyl Coating:	not determined	

#### FIRST AID MEASURES

- Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
- Skin Contact: Promptly flush skin with water until all chemical is removed.
- Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.
- Ingestion: Not a direct hazard.

#### FIRE FIGHTING MEASURES

Flash Point:	N/A
Flash Point Method:	N/A
Burning Rate:	Will not burn in the absence of an independent flame source.
Autoignition Temp:	N/A
LEL:	N/A
UEL:	N/A

Use foam, dry chemical, or water fog. Wear SCBA and appropriate PPE when exposed to products of decomposition.

6

ACCIDENTAL RELEASE MEASURES

This product requires no special spill handling procedures.



SDS Number: PI-SDS-T590



SheerWeave Style 4500/4600

Revision Date: 5/13/2015

Page 3 of 5

7

#### HANDLING AND STORAGE

Handling Precautions: Keep away from sources of ignition. Storage Requirements: Store at ambient temperature at atmospheric pressure.

8

#### EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: General mechanical room ventilation is expected to be satisfactory. Personal Protective Not required for intended use. Equip:

9	PHYSICAL AND CHEMICAL PROPERTIES
Appearance:	Textured fabric of varying colors.
Physical State:	Solid
Odor:	New vinyl
Solubility:	Insoluble in water
Viscosity:	Solid

#### 10 STABILITY AND REACTIVITY

Stability: Conditions to Avoid:	Product is stable under normal conditions. Oxidation promoting conditions (Heat, Sunlight and Air).
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Combustion will produce CO2, CO, HCN, and other hazardous products.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Data not available



# SDS

#### SheerWeave Style 4500/4600

SDS Number: PI-SDS-T590

Revision Date: 5/13/2015 Page 4 of 5

12

ECOLOGICAL INFORMATION

Data not available

## 13 DISPOSAL CONSIDERATIONS

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste of Subpart C, nor is it listed as a hazardous waste under Subpart D.

As a non-hazardous waste, it should be disposed of in accordance with local, state and federal regulations.

14

TRANSPORT INFORMATION

DOT Class: Not regulated #

Not regulated by DOT.

#### 15

#### **REGULATORY INFORMATION**

TSCA (Toxic Substance Control Act) Components of this product are listed on the TSCA inventory.
CERCLA (Comprehensive Response Compensation, and Liability Act) NOT reportable
SARA TITLE III (Superfund Amendments and Reauthorization Act) 313/312 Hazard categories: None.
313 Reportable Ingredients: None.
California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause cancer.







SheerWeave Style 4500/4600

SDS Number: PI-SDS-T590

Revision Date: 5/13/2015

Page 5 of 5

16

OTHER INFORMATION

THE INFORMATION IN THIS SAFETY DATA SHEET SHOULD BE PROVIDED TO ALL WHO WILL USE, HANDLE, STORE, TRANSPORT, OR OTHERWISE BE EXPOSED TO THIS PRODUCT. THIS INFORMATION HAS BEEN PREPARED FOR THE GUIDANCE OF PLANT ENGINEERING, OPERATIONS AND MANAGEMENT AND FOR PERSONS WORKING WITH OR HANDLING THIS PRODUCT. <u>PHIFER</u> INCORPORATED BELIEVES THIS INFORMATION TO BE RELIABLE AND UP-TO-DATE AS OF THE DATE OF PUBLICATION, BUT MAKES NO WARRANTY THAT IT IS. ADDITIONALLY, IF THIS SAFETY DATA SHEET IS MORE THAN THREE YEARS OLD, YOU SHOULD CONTACT <u>PHIFER</u> INCORPORATED AT THE NUMBER LISTED BELOW TO MAKE CERTAIN THAT THIS SHEET IS CURRENT.

PHIFER INCORPORATED P.O. BOX 1700 TUSCALOOSA, AL 35403

(205) 345-2120



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818

